



## DESCRIPTION OF STANDARD UNIT:

- Construction of powder coated steel
- Wooden casing
- Side and front glasses: double with black serigraphy
- Finishes: golden, silver or black
- 3 rows of highlighted glass shelves
- Yellow lighting
- Sliding, double glass rear doors
- Forced cooling
- Temp. range +4 - +10°C
- Automatic water evaporation
- Hygrostat (humidity reduction)

## OPTIONS:

- Version for chocolate & pralines
- For external condensing unit (AZ)\*\*
- LED lighting
- Wheels
- Ultrasonic humidifier (NAW)
- Front glass secured by the chain
- Stainless steel worktop
- Thermometer in the lamp
- Multiplexing

\* Values of daily consumption are provided for an evaporation temperature of -10°C and condensation temperature of +45°C.

\*\* Cooling power demand:  
1000 W/1mr at evaporating temp. -100C (automatic water evaporation on request)

TYPE C-1 DC	Length with sides* (mm)	Depth (mm)	Height (mm)	Useful surface (m <sup>2</sup> )	Weight (kg)	Daily consumption (kWh/24h)	Electrical Input Power** (w)	Electrical Input Power for AZ** (w)
DC CH Refrigerated								
140/CH	1360	975	1400	2.2	250	11	1100	650
CD NE Neutral								
140/CH	1360	975	1400	2.2	200	1.4	150	-

\* Values are provided for an evaporation temp. of -10°C, condensation temp. of +45°C, ambient temp of +25°C and relative humidity of 60%

